

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	1797	(717/168-178).CCLS.	US-PGPUB; USPAT	OR	OFF	2005/03/25 10:01
L2	5788	(709/220-223).CCLS.	US-PGPUB; USPAT	OR	OFF	2005/03/25 10:01
L3	7354	1 2	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/03/25 10:01
L4	3338	3 and @ad<"20000621"	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/03/25 10:02
L5	0	bootstrap\$4 near2 connect\$3 near2 client near2 server	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/03/25 10:03
L6	11	bootstrap\$4 with connect\$3 with client with server	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/03/25 10:03
L7	4	6 and @ad<"20000621"	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/03/25 10:04


[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#)^{New!} [more »](#)

bootstrap connect client to server

Search

[Advanced Search](#)
[Preferences](#)

"to" is a very common word and was not included in your search. [\[details\]](#)

Web

Results 1 - 10 of about 139,000 for **bootstrap connect client to server**. (0.37 second)

Configuring connection to a non-default bootstrap server

... localhost. port_number is one of the following ports of the **server**, which **client** applications use to **connect** to the **bootstrap server**. If ...

publib.boulder.ibm.com/infocenter/ws60help/topic/com.ibm.websphere.pmc.nd.doc/tasks/tjn0033_.html - 19k -

[Cached](#) - [Similar pages](#)

C++ Bootstrap Object Programming Reference

... do not match, the invocation to the **Bootstrap** constructor will fail ... seemingly unrelated error message: ERROR: Unofficial **connection** from **client** at <tcp/ip ...

e-docs.bea.com/wle/cref/boot.htm - 84k - [Cached](#) - [Similar pages](#)

C++ Bootstrap Object Programming Reference

... a remote **client**, this exception is raised if the **Bootstrap** object cannot **connect** to the WLE domain. The address of the WLE domain IOP **Server** Listener/Handler ...

e-docs.bea.com/wle/wle50/cref/boot.htm - 86k - [Cached](#) - [Similar pages](#)

[[More results from e-docs.bea.com](#)]

Wireless access: Windows Server 2003, Standard Edition

... **clients** by using a VLAN that contains a certificate **server**. You can also **bootstrap** wireless **clients** by using an unauthenticated Ethernet **connection** or a ...

www.microsoft.com/resources/documentation/WindowsServ/2003/standard/proddocs/en-us/sag_ias_depl_wap.asp - 25k -

[Cached](#) - [Similar pages](#)

eMule-Project.net - Official eMule Site. Downloads, Help, Docu ...

... If it cannot **connect** simply chose **Bootstrap** -> From known **clients** in the Kademlia main windows then **connect** to a **server** and start a download. ...

www.emule-project.net/home/perl/help.cgi?l=1&topic_id=308&rm=show_topic - 18k - [Cached](#) - [Similar pages](#)

Penn State Red Hat proxy server client config

Penn State Departmental Red Hat proxy **server client** config. ... q <http://redhat.moc.psu.edu/pub/bootstrap-3.0-x86> ... 2. run the command up2date to **connect** your system ...

computerstore.psu.edu/redhat-dept.htm - 10k - [Cached](#) - [Similar pages](#)

TCP Back-Channels

... There is no channel between the X **server** and any external process over which external **clients** can **bootstrap connections**. Addressing ...

www-dsg.stanford.edu/papers/firewall/node19.html - 5k - [Cached](#) - [Similar pages](#)

TCP/IP Tutorial and Technical Overview

... to respond to ARP requests) and begin the **bootstrap** process ... The **client** will execute and print out the response from the **server** as soon as the **connection** is made ...

www.auggy.mlnet.com/ibm/3376c417.html - 10k - [Cached](#) - [Similar pages](#)

Device Management

... Device Management **Bootstrap**: The way the **server** should provision the **client** so that it ... Session: The way the **server** can request the **client** to **connect** to it ...

www.aepona.com/learn_about/whitepapers3.html - 34k - [Cached](#) - [Similar pages](#)

lincs:

... the daemon it simply loads the **bootstrap** backends and ... to register for notifications without **connecting** first ... Communication between **client** and **server** takes place ...

lincs.tigris.org/lincs/architecture/architecture.html - 23k - [Cached](#) - [Similar pages](#)


[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#) ^{New!} [more »](#)

bootstrap connect client to server

Search

[Advanced Search](#)
[Preferences](#)

"to" is a very common word and was not included in your search. [\[details\]](#)

Web

Results 11 - 20 of about 139,000 for bootstrap connect client to server. (0.15 second)

Personal info for dhanson

... **bootstrap** node. The **client** will **connect** to a **bootstrap** node, which will let the **client** know the first free node of the **server**. Once I ...

nest.cs.uiowa.edu/22C178f02/person/dhanson/ - 7k - [Cached](#) - [Similar pages](#)

Understanding Java RMI Internals

... **connection** and creates a new socket just to handle this single **connection**. ... **Bootstrap Problem!!!** ... The solution depends on how we can inform the **client** about the ...

www.developer.com/java/other/article.php/3455311 - 55k - [Cached](#) - [Similar pages](#)

Implementing Your ISA Server Solution: Windows Server 2003 ...

... If you choose a direct **connection**, you need to ... or **bootstrap** protocol (BOOTP) **bootstrap** protocol (BOOTP). A protocol ... for dynamic assignment of **client** addresses. ...

www.microsoft.com/resources/documentation/ WindowsServ/2003/all/deployguide/en-us/dnsbi_per_qfsa.asp - 17k - [Cached](#) - [Similar pages](#)

[[More results from www.microsoft.com](#)]

<nobr>X-Hive/DB</nobr> 4.0 - Advanced Topics

... remote lockserver (this is specified in the remote **bootstrap** file ... for instance start the Admin-client on the **client**-host, you should be able to **connect** to a ...

support.x-hive.com/documentation4/kb_remoteaccess.html - 6k - [Cached](#) - [Similar pages](#)

[PDF] BOOTP forwarding via a BOOTP Relay Agent

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... The **Bootstrap** Protocol (BOOTP) enables a host to boot from ROM and request it's own IP address ... Here a BOOTP Relay Agent is used to **connect** the BOOTP **Client** ...

www.eventhelix.com/RealtimeMantra/Networking/Bootp.pdf - [Similar pages](#)

Linux on iPAQ with Linux

... debug \nodetach **connect** ' chat -v -s "CLIENT" "\dCLIENTSERVER\c". ... jff2, but could not make a usb-ethernet **connection**. This worked with the task-**bootstrap**.jffs2 ...

www.dorchain.net/~joerg/ipaq/ - 6k - [Cached](#) - [Similar pages](#)

User Guide To ACEDB 4_9 Sockets-based Client/Server

... To '**bootstrap**' an admin user so you can ... try accessing it using the **client**: saceclient <host_where_server_is_running ... If you can **connect** correctly then you are ...

www.acedb.org/Development/ wdoc/Socket_Server/SOCKET_aceserver.html - 28k - [Cached](#) - [Similar pages](#)

Imager

... **Clients** **connect** to the master **server** and wait for the master **server** to tell them the address and ... The fake **server** acts like a **server** to **bootstrap** the process. ...

sam.holden.id.au/junk/IMAGER/ - 7k - [Cached](#) - [Similar pages](#)

[PPT] Computer Networks

File Format: Microsoft Powerpoint 97 - [View as HTML](#)

... bootps 67 (**bootstrap** server). bootpc 68 (**bootstrap** client). http 80. kerberos 88. ... send(). **Server** Side. **Client** Side. recv(). send(). **Connect**(). **Socket**(). closesocket ...

lcassel.csc.villanova.edu/ networks/clientserver&code.ppt - [Similar pages](#)

[PDF] 1 Peer-peer Computing & CS 699/IT 818 Fall 2004 Acknowledgements

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Application-level, **client-server** protocol over point-to ... Four steps: **Connect** to Napster **server** ... leaders virtual neighbors **bootstrap** node **connecting** ...


[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#)^{New!} [more »](#)

bootstrap connect client to server

Search

[Advanced Search](#)
[Preferences](#)

"to" is a very common word and was not included in your search. [\[details\]](#)

Web

Results 21 - 30 of about 139,000 for **bootstrap connect client to server**. (0.18 second)

Administering TCP/IP and Internet services

... user name directory service Configuring **Bootstrap** Protocol (BOOTP ... Configuration of the broadcast **clients** Testing and ... Troubleshooting PPP links **Connect** to the ...
uw713doc.sco.com/en/NET_tcpip/CONTENTS.html - 54k - [Cached](#) - [Similar pages](#)

An Introduction to Programming with JacORB

... This **bootstrap** file has to be available to **clients** networkwide, so ... network domain which allows read access to the **bootstrap** file over a HTTP **connection**. ...
www.huihoo.com/corba/jacorb/tutorial.html - 22k - [Cached](#) - [Similar pages](#)

CMSC 417-S05 NOTES ON CHAPTER 2: APPLICATION LAYER SHANKAR ...

... and a **server** (storing and serving content to **clients**). ... Peers have dynamic Internet **connectivity** and IP ... OF ACTIVE PEERS: - Have "**bootstrap**" **servers**: always-up ...
www.cs.umd.edu/~shankar/417-Notes/krNotes-ch2.txt - 9k - [Cached](#) - [Similar pages](#)

myITforum.com : SMS 2003 SP1 Advanced **Client** Requirements

... ADMIN\$ share in order for ccmsetup to **bootstrap** the **client.msi** down to the advanced **client**. ... IPC\$ share is used with temporary **connections** between **clients** ...
myitforum.techtarget.com/articles/8/view.asp?id=8215 - 27k - [Cached](#) - [Similar pages](#)

[PDF] Chapter 2 Application Layer Chapter 2: Application Layer

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Persistent HTTP Multiple objects can be sent over single TCP **connection** between **client** and **server**. HTTP/1.1 uses persistent **connections** in default mode Page 10. ...
www.im.ntu.edu.tw/~sunny/2003_slides/NW/chapter2-2.pdf - [Similar pages](#)

Java Forums - Unable to **connect** to an EJB fom a standalone java ejb ...

... Re: Unable to **connect** to an EJB fom a standalone java ejb **client** Author: bab, ... Make sure that any **bootstrap** address information in the URL is correct and that ...
forum.java.sun.com/thread.jspa?threadID=589860&tstart=225 - 38k - [Cached](#) - [Similar pages](#)

Configuring the **Client** Applications

... that **client** systems will need to allow **connections** on port ... keys for registering and configuring **client** systems that ... To do this, create a **bootstrap.sh** file much ...
www.redhat.com/docs/manuals/RHNetwork/client-config/3.6/latest-clients-configuring.html - 20k - [Cached](#) - [Similar pages](#)

[PDF] The Dynamic Host Configuration Protocol (DHCP)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... DHCP is based on the older **Bootstrap** Protocol (BOOTP) [5 ... in to a network **connection** and **connect** to Internet ... The **client** listens on and sends all the messages ...
www.cs.hut.fi/~ijs/dhcp/dhcp.pdf - [Similar pages](#)

Planning WebLogic **Server** Clusters

... More importantly, when **clients** **connect** directly to a ... a firewall, the initial **bootstrap** **server** becomes a ... point of failure for the entire **client** **connection**. ...
www.weblogic.com/docs51/cluster/planning.html - 45k - [Cached](#) - [Similar pages](#)

Kademlia-MoDs.de - eMule Original **Client** Download

... Auto Kad **bootstrap** if you are trying to **connect** and see a ... Unk: **Bootstrap** selectable by IP:Port or by a known Kad ... your known **client** list for a Kad **client** to boot ...
www.kademlia-mods.de/?mods=original&page=7 - 16k - [Cached](#) - [Similar pages](#)


[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#) ^{New!} [more »](#)

bootstrap connect client to server

Search

[Advanced Search](#)
[Preferences](#)

"to" is a very common word and was not included in your search. [\[details\]](#)

Web

Results 31 - 40 of about 139,000 for bootstrap connect client to server. (0.13 second)

Cisco Element Management System Installation and Configuration ...

... These **clients** must use a stringified IOR to **bootstrap** the **connection**

to the Naming Service, as described below. ...

www.cisco.com/.../netmgts/ps829/products_installation_and_configuration_guide_chapter09186a00801a8811.html - 101k -

[Cached](#) - [Similar pages](#)

[PDF] Wide-Area Communication for Grids: An Integrated Solution to ...

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... we distinguish between standard TCP **client/server** handshake, symmetrical ... goal is to **connect** under various ... purposes of data, service, and **bootstrap** **connections**. ...

hpdc13.cs.ucsb.edu/papers/33.pdf - [Similar pages](#)

[PPT] Part I: Introduction

File Format: Microsoft Powerpoint 97 - [View as HTML](#)

... excessive query traffic. query radius: may not have content when present. **bootstrap** node still required. ... **client-server** paradigm. ... **connection-oriented**, reliable: TCP ...

crystal.uta.edu/~zaruba/CSE5344/chapter2b.ppt - [Similar pages](#)

[jonas] [joram] Configuring JORAM in Cluster

... org.objectweb.jonas.**server.Bootstrap.main(Bootstrap.java:102 ... 507)** at java.net.Socket.

connect(Socket.java ... at fr.dyade.aaa.jndi2.**client.SimpleNamingConnection.open ...**

mail-archive.objectweb.org/jonas/2005-01/msg00126.html - 16k - [Cached](#) - [Similar pages](#)

[PDF] Peer to Peer Computing

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Application-level, **client-server** protocol over point-to-point TCP ... **bootstrap** node ... peer-to-peer networking: applications **connect** to peer applications ...

cs.gmu.edu/~setia/cs475-S03/slides/p2p.pdf - [Similar pages](#)

mpi-dynamic Mailing List Archive: Re: **client/server**

... MPI uses this descriptor to **bootstrap** MPI communication > between ... call is exactly the same for **client** and **server** ... who did bind+listen+accept and who did **connect**. ...

www.mpi-forum.org/archives/mail/mpi-dynamic/0197.html - 9k - [Cached](#) - [Similar pages](#)

[PDF] Chapter 2 Second Edition

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... 11 Page 12. TCP **connection** establishment TCP 3-way handshake: r **client** sends to **server** TCP segment with SYN bit is set. r **server** responds with segment that has ...

cis.poly.edu/~ross/tutorials/CDNtutorial.pdf - [Similar pages](#)

OpenP2P.com: Backlash!

... between **client-server** and peer-to-peer is, since the two-way Web moves power to the edges of the network while Napster and ICQ **bootstrap** **connections** from a big ...

www.openp2p.com/pub/a/p2p/2001/04/05/shirky.html?page=last&x-maxdepth=0 - 51k - [Cached](#) - [Similar pages](#)

BBPC News | BuildOrBuy - Windows Network Protocols

... to BOOTP requests from a **Client** with the **Client** IP Address ... **BootStrap**: PC **BootStrap** (For Reference). Bridge (Network Bridge): A device **connecting** two LAN segments ...

www.buildorbuy.org/networkprotocols.html - 39k - [Cached](#) - [Similar pages](#)

[PDF] CORBA, Java, C++ and ODBMS for Distributed Web Computing

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Additional demands for preserving pending **connections** or for ... Maintenance of the **client**


[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#)^{New!} [more »](#)

bootstrap connect client to server

Search

[Advanced Search](#)
[Preferences](#)

"to" is a very common word and was not included in your search. [\[details\]](#)

Web

Results **41 - 50** of about **139,000** for **bootstrap connect client to server**. (0.20 second)

RHN Satellite Server 3.6 Release Notes

... Within the **Connection Errors** section of the Troubleshooting chapter ... the commands for checking the **client** and **server** ... The sample **bootstrap** script in Appendix A of ...

www.redhat.com/docs/manuals/RHNetwork/release-notes/3.6.0/sat-release-notes.html - 26k - [Cached](#) - [Similar pages](#)

[[More results from www.redhat.com](#)]

omniORB configuration and API

... default = 900 The port number for the obsolete Sun **bootstrap** agent. ... the rules about whether a **server** should accept an incoming **connection** from a **client**. ...

omniorb.sourceforge.net/omnipy2/omniORBpy/omniORBpy004.html - 32k - [Cached](#) - [Similar pages](#)

ONJava.com: Developing Highly Distributed Applications with Jtrix

... as a parameter and used it to **connect** to the ... We get the node's output ("**Bootstrap** starting," etc.), the service ... has shown how to write a Jtrix **client** and **server** ...

www.onjava.com/pub/a/onjava/2002/05/08/jtrix.html?page=last - 48k - [Cached](#) - [Similar pages](#)

api: First Steps

... from the class com.sun.star.comp.helper.**Bootstrap**. ... Now the **client** holds a reference to the remote ... Professional UNO - UNO Concepts - UNO Interprocess **Connections** ...

api.openoffice.org/docs/DevelopersGuide/FirstSteps/FirstSteps.htm - 101k - Mar 23, 2005 - [Cached](#) - [Similar pages](#)

[PDF] Microsoft PowerPoint - chap2_2ed_5July02

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Persistent HTTP □ Multiple objects can be sent over single TCP **connection** between **client** and **server**. □ HTTP/1.1 uses persistent **connections** in default mode ...

www.cise.ufl.edu/~sgchen/cen4500spring2005/chap2_2ed_5July02.pdf - [Similar pages](#)

[PDF] SUGI 23: Overview of Java Components and Applets in SAS/IntrNetT ...

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... After the **bootstrap** program has successfully started the SAS/CONNECT **server**, the Java **client** can **connect** to the **server** and start sending requests. ...

www2.sas.com/proceedings/sugi23/Internet/p156.pdf - [Similar pages](#)

Introducing WebLogic Enterprise Connectivity

... **Bootstrap** establishes communication between a **client** application and ... of WLEC are: Pooled IOP **connections** to the ... Multiple active WLE **client** transactions from a ...

www.weblogic.com/docs51/classdocs/API_wlec_intro.html - 24k - [Cached](#) - [Similar pages](#)

[[More results from www.weblogic.com](#)]

Client

... which this **client** is currently configured to **connect** to the ... Returns the RunQueue in use by this **client**. ... Class sclass) Returns the first **bootstrap** service that ...

threerings.net/code/narya/narya/docs/api/com/threerings/presents/client/Client.html - 65k - [Cached](#) - [Similar pages](#)

[PDF] Microsoft PowerPoint - handout-content-distribution.ppt

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Intermittently connects to Internet; gets new IP address for each **connection** ...

Alice's peer is both a Web **client** and a transient Web **server**. ... **bootstrap** node ...

www.eecs.umich.edu/~farnam/498/handout-content-distribution.pdf - [Similar pages](#)

Wide-Area Communication for Grids: An Integrated Solution to ...

... Crosses firewalls, no, yes, yes, yes. NAT support, **client**, partial, yes, yes. For

bootstrap, yes, no, no, yes. ... Table 1: **Connection** establishment methods summary. ...



Web Images Groups News Froogle Local^{New!} more »

bootstrap connect client to server

Search

Advanced Search
Preferences

"to" is a very common word and was not included in your search. [\[details\]](#)

Web

Results 51 - 60 of about 139,000 for bootstrap connect client to server. (0.28 second)

[\[PDF\] BOOTP forwarding via a BOOTP Relay Agent](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... The **Bootstrap** Protocol (BOOTP) enables a host to boot from ROM and request it's own ... Here a BOOTP Relay Agent is used to **connect** the BOOTP Client to BOOTP ...

www.eventhelix.com/EventStudio/arp_bootp_dhcp_icmp/BOOTP%20Sequence%20Diagram.pdf - [Similar pages](#)

[FrontBase](#)

... When a **client** wants to **connect** to a cluster it ... **server** being started will attempt to **connect** to the ... **servers** should be included in the **bootstrap** procedure for ...

www.frontbase.com/.../FrontBase.woa/2/wa/supportPage?currentPage=TechnicalNotes&itemId=1000005 - 6k -

[Cached](#) - [Similar pages](#)

[\[PDF\] Internet and Intranet Protocols and Applications](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Separates commands from data • **Client** can send commands during data transfer ... **Server** closes all **connections**. ... Often used for **bootstrap**; eg, ROM-based ...

www.cs.nyu.edu/artg/internet/Spring2003/lectures/lec_6.pdf - [Similar pages](#)

[ActiveMQ - Topologies](#)

... where there is no **server** - just **clients** **connecting** together. ... in production and have well known **servers** fixed on ... peer to peer topology as a **bootstrap** to create ...

activemq.codehaus.org/Topologies - 18k - [Cached](#) - [Similar pages](#)

[Internet Draft Jesse Walker Expiration: December 2002 Amol ...](#)

... In some cases the **bootstrap** policy will identify the authorized ... object, it SHOULD assume that the **client** wishes to open a non-secure **connection** and proceed ...

www.ietf.org/proceedings/02jul/I-D/draft-ietf-rap-cops-tls-04.txt - 26k - [Cached](#) - [Similar pages](#)

[Internet Draft Jesse Walker Expiration: May 2004 Amol Kulkarni, Ed ...](#)

... with the **server**, it SHOULD first **connect** to the non-secure port, and send a **Client** Open message with a ClientType=0. '**Bootstrap**' policies implemented on the ...

www.ietf.org/proceedings/04mar/I-D/draft-ietf-rap-cops-tls-07.txt - 30k - [Cached](#) - [Similar pages](#)

[\[More results from www.ietf.org \]](#)

[The FreeBSD Diary – Bacula: Cross-Platform Client-Server Backups](#)

... File Messages = Standard Pool = Default Write **Bootstrap** = "/var/db ... example.org:9102

Failed to **connect** to **Client** ... I was running a **client-only** installation of ...

www.freebsdidiary.org/bacula.php - [Similar pages](#)

[Bootstrapping](#)

... to be able to do an automated **bootstrap** from the ... Then I have my **server** **connect** and retrieve the key ... Because my **client** already knows the **server**, the **connection** ...

lists.gnu.org/archive/html/help-cfengine/2004-02/msg00067.html - 14k - [Cached](#) - [Similar pages](#)

[man: PerlObjCBridge](#)

... qw(Exporter DynaLoader); @EXPORT = qw(); \$VERSION = '1.0'; **bootstrap** AddSystem \$VERSION ... **Clients** can then look up the name "AddServer" to **connect** to this ...

www.hmug.org/man/3/PerlObjCBridge.html - 28k - [Cached](#) - [Similar pages](#)

[Welcome to Ardence](#)

... The **bootstrap** emulates a hard drive by directing disk ... systems on the fly by **connecting** **clients** to the ... can stream to Windows 2000 Professional and XP **clients**. ...

www.vci.com/enterprise/news.aspx?ID=271 - 17k - [Cached](#) - [Similar pages](#)



Web Images Groups News Froogle Local ^{New!} more »

bootstrap connect client to server

Search

Advanced Search
Preferences

"to" is a very common word and was not included in your search. [\[details\]](#)

Web

Results 61 - 70 of about 139,000 for bootstrap connect client to server. (0.15 second)

ONLamp.com: Bacula: Cross-Platform Client-Server Backups

... a Director that is allowed to **connect** to this **Client**. ... Job { Name = "Client1" Type =

Backup Client = laptop-fd ... Standard Pool = Default Write **Bootstrap** = "/var/db ...

www.onlamp.com/pub/a/onlamp/2004/01/09/bacula.html - 53k - Mar 23, 2005 - [Cached](#) - [Similar pages](#)

[PDF] Microsoft PowerPoint - rooney.ppt

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... How it works: – **bootstrap**: **connect** to a well-known peer ... large overhead for maintaining enough peer **connections** due ... Booster Box **Client Server** Page 26. ...

www.ibr.cs.tu-bs.de/events/netgames2002/presentations/rooney.pdf - [Similar pages](#)

[PDF] Using Red Hat Network Satellite Server to Manage Dell PowerEdge ...

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... in the setup is to create a **bootstrap** script. This script can greatly simplify the **client** systems' configuration and **connection** to the Satellite **Server**. ...

www.dell.com/downloads/global/solutions/Approved-RedHatSatelliteServer-TechReportVersion.pdf - [Similar pages](#)

[PPT] chap2_2ed_5July02

File Format: Microsoft Powerpoint 97 - [View as HTML](#)

... **connection**-oriented: setup required between **client** and **server** processes. ... Multiple objects can be sent over single TCP **connection** between **client** and **server**. ...

www.cise.ufl.edu/~sgchen/cen4500spring2005/chap2_2ed_5July02.ppt - [Similar pages](#)

[PDF] Application Layer Protocols 2

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... terminal driver TCP/ IP telnet **client** pseudo terminal driver TCP/ IP telnet **server** shell Page 17. 17 rlogin **Connection** between UNIX systems port 513 ...

icawww1.epfl.ch/sc250_2004/lecture_notes/sc250_04_4.pdf - [Similar pages](#)

[Gnused-update] - cleanup

... py 1.24 gnused gnused/**client**/pycommon/gmLoginInfo ... NOT drop supporting readonly **connections** on > 7.3) gnused gnused/**server/bootstrap/bootstrap**-archive.conf ...

lists.gnu.org/archive/html/gnused-update/2004-07/msg00015.html - 8k - [Cached](#) - [Similar pages](#)

[\[More results from lists.gnu.org \]](#)

[OB-Users] Narrowing problems using corbaloc

... was unable to make a secure **connection** to the ... Usually, in this case because the **client** couldn't ... corbaloc = "corbaloc::127.0.0.1:2000/**bootstrap**"; > > > org.omg ...

mail.ooc.nf.ca/pipermail/ob-users/2000-November/013570.html - 7k - [Cached](#) - [Similar pages](#)

[PDF] Microsoft PowerPoint - Application.ppt

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... in firmware Often uses to **bootstrap** workstations and ... Sender is a **client** (Outlook, Sendmail, a mail **server**, ...) and establishes a TCP **connection** (port 25 ...

aot.ce.unipr.it/team/poggi/teaching/rc/docs/Application-6sp.pdf - [Similar pages](#)

[PDF] Microsoft PowerPoint - Application.ppt

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Often uses to **bootstrap** workstations and network devices ... Sender is a **client** (Outlook, Sendmail, a mail **server** ... and establishes a TCP **connection** (port 25) to the ...

aot.ce.unipr.it/team/poggi/teaching/rc/docs/Application.pdf - [Similar pages](#)

[\[More results from aot.ce.unipr.it \]](#)